

DATA SHEET

F600 SNAP AND CONTINUOUS BUSINESS FORMS COLLATOR



DESCRIPTION

The **F600** rotary business forms collator is a “Work Horse” . The F600 has a production speed of 550 f.p.m and will run continuously for extended periods of time. It is designed with sturdy 1 1/2” side frames, the latest electronic run controls and the sturdiest of components for long term performance. It is capable of both unit set and/or continuous processing and features a self storing folder, crash numbering, skip or continuous cold glue and ease of operation. Changeover from unit set to continuous can be accomplished in under ten minutes.

BASIC FEATURES (Four Station)

- Minimum Web Width 3”
- Max. Web Width 18”
- Maximum Paper Roll Diameter 24”
- Max. Carbon Roll Diameter 16”
- Four 24” Paper Unwind Spindles
- Three 18” Carbon Unwind Spindles
- Pneumatic Braking for Paper Unwinds
- Pneumatic Braking for Carbon Unwinds
- Flo Master Cold Glue System
- Variable Crash Numbering 17” - 24”
- Two Cutoff & Down Only Perf Cylinders
- Crimp Lock Section 8.5” & 12”
- Slide-A-Way Folder W/2 gear Changes
- Unit Set Batch Delivery
- Common Creeper Delivery Table
- Electronic Counter
- 5 HP Drive Motor and Controls
- Jog/Run/Stop/ Remote Control

OPTIONS

- Additional Unwind Sections
- Up & Down Perf and Cutoff Heads
- Quick Change Perf Blade Bars
- Glue Impactor System
- Lateral Adjustments for Paper Spindles
- Lateral Adjustments for Carbon Spindles
- Cams and Mounting Rings for Numbering Unit
- Trim Disposal System
- Roll Up Folder
- Electric Hoist for Head Change
- Automated Batcher Stacker
- Cross Web Glue System

Technical specifications subject to change.

Form Flo 

FORM NUMBER f600 - 05/03